

Portable Flue gas



- ❖ IPS TOUCH SCREEN DISPLAY
- ❖ REAL-TIME-CLOCK AND DATE
- ❖ HIGH ACCURACY
- ❖ LOW MAINTANANCE
- ❖ DRIFT FREE, OPTICAL MESUREMENT

TECHNICAL SPECIFICATION:

- Type: Portable
- Model: SE 4000
- Measure principle: Electro – Chemistry / PID
- Display: Color TFT
- Data Log: Through SD card
- Measure ranges: O₂: 0 – 25 %, CO: 0 - 2000 ppm, SO_x 0 - 2000 ppm, NO_x 0 - 1000 ppm, VOC 0-1000 ppm, etc.
- Resolution: 0.1
- Accuracy: +/- 2% FS.
- Response time: 90% of the value in less than 60 seconds
- Frequency of recommended measure: >5 s
- Stoking temperature: -10°C to + 60°C
- Signal interface: Modbus RS-232, TCP/IP
- Power-supply: 24V Battery
- Backup on continuous use: 8 hours
- Charging time: 1 hour (From Min to Max)

**Shri Pramukh Swami Industrial Estate, Shed # C-1/389, Second Floor,
Office # 8, 9, 10, 11, 12, 13 GIDC Makarpura, Vadodara – 390010, Gujarat, India.**

Mob. no: +91 74900 43126

Email: ho@sewater.in, Web: www.sewater.in

APPLICATIONS:

- Process Stack Monitoring.
- Emission Stack Monitoring

DELIVERY CONTENT:

- Instrument.
- Sample probe with filter.
- User manual.
- Carrying cover.

**Shri Pramukh Swami Industrial Estate, Shed # C-1/389, Second Floor,
Office # 8, 9, 10, 11, 12, 13 GIDC Makarpura, Vadodara – 390010, Gujarat, India.
Mob. no: +91 74900 43126
Email: ho@sewater.in, Web: www.sewater.in**